

# B & C

— NarrowStack —



B&C NarrowStack Basic

## NarrowStack

# Ready to serve 24 HOURS A DAY

## THE SMART VEND COLD DRINKS VENDING MACHINES

- Easy programming using selection button sequence
- Electronic control and data-recording
- Energy Management by real time clock
- Each column driven via individual vend motor
- 24 V DC motors
- Interchangeable parts
- Quadruple loading for 0.33 l cans and double loading for 0.50 l PET bottles up to 245 mm height



NarrowStack BASIC offers NarrowStack technology at competitive price.  
**A great value for price and quality!**



MODEL	NARROWSTACK BASIC SVE 480-7 DD	NARROWSTACK BASIC SVE 550-8 DD	NARROWSTACK SVE 476-7 DD	NARROWSTACK SVE 544-8 DD	NARROWSTACK SVE 680-10 DD
DIMENSIONS H x W x D (mm)	1830 x 750 x 940	1830 x 850 x 940	1830 x 750 x 940	1830 x 850 x 940	1830 x 1010 x 940
WEIGHT (NET - Standard machine without options)	310 kg	335 kg	310 kg	335 kg	390 kg
NO. OF SELECTIONS / COLUMNS	7 / 7	8 / 8	10 / 7	10 / 8	10 / 10
MAX. PRODUCT LENGTH (mm)	505	505	505	505	505
MAX. PRODUCT DIAMETER (mm)	72	72	72	72	72
PROTOCOL	Executive / MDB	Executive / MDB	Executive / MDB	Executive / MDB	Executive / MDB
COOLING SYSTEM CONTROL	Thermostat	Thermostat	Electronic	Electronic	Electronic
REFRIGERATION POWER	520 W / 10 cc	520 W / 10 cc	997 W / 14 cc	997 W / 14 cc	997 W / 14 cc
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C	+2°C up to +10°C	+2°C up to +10°C	+2°C up to +10°C	+2°C up to +10°C
MAX. POWER CONSUMPTION	580 W	580 W	800 W	800 W	800 W
POWER SUPPLY	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz

CAPACITIES					
CAN 0,33 l	476	544	476	544	680
PET BOTTLE 0,50 l	238	272	238	272	340



#### OPTION LIST

- ▶ CUSTOMISED CABINET & DOOR COLOUR
- ▶ TWO-LINE LCD DISPLAY
- ▶ STACK ASSEMBLY FOR PRODUCT Ø 74 mm
- ▶ SECURITY CASH SYSTEMS
- ▶ LOADING RACK (ONLY FOR BASIC MODEL)
- ▶ SAFETY COIN INSERT
- ▶ WALL / FLOOR FIXING KIT
- ▶ SPECIAL CODED LOCK (RIELDA)
- ▶ WEATHER PROTECTION
- ▶ BRANDING

#### STANDARD CABINET COLOURS

